

FURUNO

AIS
Automatic Identification System



Model:
FA-170


*The FURUNO FA-170 AIS
presents data
for collision avoidance
with its easy-to-use interface*

AIS
Automatic Identification System



- ▶ Class A AIS transponder
- ▶ Clear 4.3" color display
- ▶ Displays information about the AIS-equipped ships, as well as, coastal stations and Aids to Navigations within VHF coverage
- ▶ Outputs AIS data to ECDIS, radar and other navigational equipment for collision avoidance support
- ▶ Sufficient output ports for dual configuration of ECDIS and radar system
- ▶ LAN interface available for efficient network integration into a bridge system
- ▶ BAM (Bridge Alert Management) ready
Meets the specific requirements for alerts and interconnection with Bridge Alert Management as specified in IMO MSC.302 (87).
- ▶ Optional pilot plug available
- ▶ Receives AIS-SART signals for assisting in streamlining SAR activities

Plotter display



Displays symbols for AIS-equipped ships, base stations, AIS-SARTs, and so on. When you select a certain target, the information about the ship (MMSI (or name, when available), heading, SOG, COG, etc.) is displayed.

AIS symbols

	Own ship symbol		AIS base station		AIS-SART/MOB-AIS/EPIRB-AIS
	Target		Aid to Navigation (physical)		SAR aircraft
	Selected target		Aid to Navigation (virtual)		SAR vessel




Target list

The FA-170 can store up to 2048 AIS targets and AIS-SARTs.

MMSI : 201506120				
TARGET LIST 00:00:43 1-8(400)				
NAME/MMSI/TYPE	RNG[NM]	BRG[°]	AGE[']	
300000001	1.0	000.0	1	
DUMMY_NAME_NO.2	1.1	010.0	2	
DUMMY_NAME_NO.3	1.2	020.0	3	
BS:300000004	1.3	030.0	4	
SAR:111273222	1.4	040.0	5	
SAR:111273101	1.5	050.0	6	
300000007	1.6	060.0	7	
DUMMY_NAME_NO.8	1.7	070.0	8	

Quick-access functions

When you select one target from the list and press [ENT] key, the pop-up window is generated.



The FA-170 displays the detailed information on the selected target. Also, you can create an AIS message or send a name request to the target ship.

Dangerous target list

The dangerous target list displays the name and particulars of targets classified as dangerous targets.

MMSI : 201507310				
DANGEROUS LIST 00:02:39 1-8(100)				
NAME/MMSI/TYPE	RNG[NM]	BRG[°]	AGE[']	
300000001	1.0	000.0	1	
DUMMY_NAME_NO.2	1.1	010.0	2	
DUMMY_NAME_NO.3	1.2	020.0	3	
BS:300000004	1.3	030.0	4	
SAR:111273222	1.4	040.0	5	
SAR:111273101	1.5	050.0	6	
300000007	1.6	060.0	7	
DUMMY_NAME_NO.8	1.7	070.0	8	

Own ship information

Displays own ship's position, heading, ROT, COG, SOG, destination, ship size, MMSI, name, and so on.

MMSI : 201507310	
OWN INFORMATION	
UTC	31/JUL/2015 12:00:00
POSN	34°44.5005'N 135°21.3021'E
ROT	0.0°/min
SOG	12.3kn
HDG	130°
COG	135.0°

MMSI : 201506050	
OWN INFORMATION	
NAV STATUS	12 PIR-DRIVEN VESSEL PUSHING AHEAD OR TOWING ALONGSIDE
DESTINATION	KOBE
ETA(UTC)	01/JAN 12:34
NO. OF PERSONS	100

MMSI : 201506050	
OWN INFORMATION	
MMSI	201 506 050
NAME	SHIPNAME
IHO NO.	1073741823
CALL SIGN	=SEVEN=
TYPE OF SHIP	024 FERRY
VENDOR ID	FEC-02-123456

MMSI : 201506050	
OWN INFORMATION	
SHIP SIZE	120m
BEAM	60m
ANT POSN	Y 60m X 0m
INTERNAL	80m
EXTERNAL	10m
DRAUGHT	0.0m

MMSI : 201506120	
DESTINATION LIST	
01:	KOBE
02:	YOKOHAMA
03:	BUSAN
04:	SEATTLE
05:	SAN FRANCISCO
06:	BRISBANE
07:	= NO ENTRY =
08:	= NO ENTRY =

When you enter the voyage-related data, you can select a destination from the list. Up to 20 destination names can be preset on the list. Cut, copy and paste functions are available while editing the list.

Alert list

Displays all (current and past) alerts


MMSI : 201506120	
ALERT	
LIST:0	LOG:11
TIME(UTC)	ALERT
30/JAN 17:20	TX MALFUNCTION
29/JAN 17:20	ANTENNA VSWR EXCEEDS LIMIT
28/JAN 17:20	RX CHANNEL 1 MALFUNCTION
27/JAN 17:20	RX CHANNEL 2 MALFUNCTION
26/JAN 17:20	GENERAL FAILURE
25/JAN 17:20	ACTIVE AIS-SART
ID:001	TX MALFUNCTION

MMSI : 201506120	
ALERT	
LIST:0	LOG:9
TIME(UTC)	ALERT
01: 01/APR 10:49	TX MALFUNCTION
02: 01/APR 10:48	TX MALFUNCTION
03: 01/APR 10:47	TX MALFUNCTION
04: 01/APR 10:46	TX MALFUNCTION
05: 01/APR 10:45	TX MALFUNCTION
06: 01/APR 10:44	ANTENNA VSWR EXCEEDS LIMIT
ID:001	TX MALFUNCTION

Short safety-related messages

MMSI : 201506120	
MSG BOX (TEXT)	
OUTBOX:9	INBOX:18
TIME(UTC)	FROM
08/APR 09:45	200000000
08/APR 09:44	200000001
08/APR 09:43	200000002
08/APR 09:42	200000003
08/APR 09:41	200000004
08/APR 09:40	200000005
08/APR 09:39	200000006

Short safety-related messages can be exchanged with a specified MMSI or all AIS-equipped ships via VHF channels. The FA-170 can store up to 20 transmitted messages and up to 20 addressed received messages and 20 broadcast received messages.



When you select one message and press [ENT] key, the pop-up window is generated where the message contents can be viewed and reply messages can be created for transmission.

SPECIFICATIONS

GENERAL

Product Name	U-AIS TRANSPONDER
Reporting capacity	2250 reports per minute on 1 channel 4500 reports per minute on 2 channels
Standards	IMO MSC.74(69) ANNEX 3, IMO MSC.302(87), IMO A.694(17), IMO MSC.191(79), ITU-R M.1371-5, DSC ITU-R M.825-3, IEC61993-2 Ed. 3, IEC60945 Ed. 4 CORRIGENDUM 1, IEC 62288 Ed. 2, IEC 61162-1 Ed. 5, IEC 61162-2 Ed. 1, IEC61162-450 Ed. 2, IEC62923-1/-2 Ed. 1

TRANSPONDER UNIT

TX/RX frequency	156.025 to 162.025 MHz
Bandwidth	25 kHz
Output power	1 W or 12.5 W selectable
DSC receiver	156.525 MHz, CH70 fixed

INTERFACE

COM port	6 ports input/output, IEC61162-1 Ed. 5 / IEC61162-2 Ed. 1
SENSOR port	3 ports input only, IEC61162-1 Ed. 5
LAN	1 port, IEC61162-450 Ed. 2, 100 Base-TX, Auto MDI/MDIX
Alarm output	1 port, Relay contact (select from Normally closed (default) or Normally open), Alarm ACK

GPS RECEIVER

Receiving channels	12 channels parallel, 12 satellites tracking
RX frequency	1575.42 MHz
RX code	C/A code
Position accuracy	GPS: less than 13 m (2 drms, HDOP<4) DGPS: less than 5 m (2 drms, HDOP<4)

VHF ANTENNA

50 Ω Single dipole antenna

MONITOR UNIT

Screen size	4.3-inch color LCD, 480 x 272 dots (WQVGA)
Viewing area	95.04 (W) x 53.856 (H) mm
Brightness adjustment	18 steps

POWER SUPPLY

Transponder unit	12-24 VDC 6-3 A
Monitor unit	12 VDC 0.3 A max. (supplied by Transponder unit)
AC/DC Power Supply Unit PR-241 (option)	100/110/200/220 VAC, 1ø, 50/60 Hz

ENVIRONMENT

Ambient Temperature	Transponder unit/Monitor unit/ Pilot plug unit/Power supply unit	-15 to +55°C
	GPS/VHF combined antenna/GPS antenna	-25 to +70°C
Relative humidity	93% or less at 40°C	
Degree of protection	Transponder unit	IP22 at bulkhead mount, IP20 at floor
	Monitor unit	IP22, IP35 with optional Waterproofing kit
	Pilot plug unit	front panel: IP22
Vibration	GPS/VHF combined antenna/GPS antenna	IP56

EQUIPMENT LIST


Standard

1	Transponder unit	FA-1701	1 unit	] Selectable
2	Monitor unit	FA-1702	1 unit	
3	GPS/VHF combined antenna and Distributor unit	GVA-100-T and DB-1	1 set	
4	GPS antenna	GPA-017S	1 unit	

Option


1	Antenna cable kit for GPS/VHF combined antenna or GPS antenna (30/40/50 m)	
2	Antenna base (for pipe mount/offset bracket/deck mount/handrail mount)	
3	VHF antenna	CX4-3/FEC
4	Power supply unit	PR-241
5	Pilot plug unit	FA-1703
6	AD converter	AD-100
7	Sub monitor unit	FA-1702
8	Flush mount kit for Monitor unit	OP24-35
9	Monitor flush mount kit for retrofitting from FA-150	OP05-140
10	Waterproofing kit for Monitor unit (IP35)	OP05-139

INTERCONNECTION DIAGRAM




Monitor unit (flush mount)

FA-1702 0.6 kg, 1.3 lb




Monitor unit (hanger)

FA-1702 0.7 kg, 1.5 lb




GPS/VHF combined antenna GVA-100-T

3.3 kg, 7.3 lb




Transponder unit

FA-1701 3.0 kg, 6.6 lb



GPS antenna GPA-017S

0.12 kg, 0.3 lb



All brand and product names are registered trademarks, trademarks or service marks of their respective holders.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

FURUNO ELECTRIC CO., LTD.
Japan | www.furuno.com

FURUNO U.S.A., INC.
U.S.A. | www.furunousa.com

FURUNO PANAMA S.A.
Republic of Panama | www.furuno.com.pa

FURUNO (UK) LIMITED
U.K. | www.furuno.co.uk

FURUNO NORGE A/S
Norway | www.furuno.no

FURUNO DANMARK A/S
Denmark | www.furuno.dk

FURUNO SVERIGE AB
Sweden | www.furuno.se

FURUNO FINLAND OY
Finland | www.furuno.fi

FURUNO POLSKA Sp. z o.o.
Poland | www.furuno.pl

FURUNO DEUTSCHLAND GmbH
Germany | www.furuno.de

FURUNO FRANCE S.A.S.
France | www.furuno.fr

FURUNO ESPAÑA S.A.
Spain | www.furuno.es

FURUNO ITALIA S.R.L.
Italy | www.furuno.it

FURUNO HELLAS S.A.
Greece | www.furuno.gr

FURUNO (CYPRUS) LTD
Cyprus | www.furuno.com.cy

FURUNO EURUS LLC
Russian Federation | www.furuno.ru

FURUNO SHANGHAI CO., LTD.
China | www.furuno.com/cn

FURUNO CHINA CO., LTD.
Hong Kong | www.furuno.com/cn

FURUNO KOREA CO., LTD
Korea

FURUNO SINGAPORE
Singapore | www.furuno.sg

PT FURUNO ELECTRIC INDONESIA
Indonesia | www.furuno.id

FURUNO ELECTRIC (MALAYSIA) SND. BHD.
Malaysia | www.furuno.my

A-2111CAS
Catalogue No. CA00001546